

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Generic Description:	Physical	Silicone Compound	PCI-Promatec
	Form:	Viscous Liquid/Dry Powders*	11707 West Sam Houston Parkway South Suite K
	Color:	Off-White**	Houston, TX 77031
	Odor:	Not available	281-933-7222

*When supplied as separate components. See sections 3 and 11 of this MSDS.

**After combining of separate components, when supplied pre-blended. See Section 9 for separate components.

SECTION 2. CHEMICAL COMPOSITION & DATA

<u>CAS number</u>	<u>Wt % *</u>	<u>Wt % **</u>	<u>Component Name</u>
14808-60-7	>99%	15.0 – 20.0	Crystalline Silica (Quartz)
1344-28-1	<1%	<1%	Aluminum Oxide
13463-67-7	<1%	<1%	Titanium Oxide
1309-37-1	<1%	<1%	Iron Oxide
63148-57-2	7.0 – 13.0	<11%	Methylhydrogen siloxane
68037-59-2	1.0 – 5.0	<5%	Dimethyl, methylhydrogen siloxane

HMIS Profile: Health: *,0** Flammability 1 Reactivity 0 Protective Equipment E*,C**

NFPA Profile: Health: 0 Flammability 1 Reactivity 0

* When supplied as separate components. See sections 3 and 11 of this MSDS.

** When supplied premixed.

SECTION 3. EFFECTS OF OVEREXPOSUREAcute Effects:

Eye: Direct eye contact may cause temporary redness and discomfort. Crystalline silica (quartz) may cause abrasion of the cornea.

Skin: No significant irritation expected from a single short-term exposure, (combined components). For the dry powders, when supplied as separate components, avoid prolonged, repeated or excessive contact with skin; may cause drying or irritation. Seek medical attention if irritation persists.

Inhalation: Low ingestion hazard in normal use. Although unlikely, if a gross ingestion of the dry powders occurs, when supplied as separate components, seek medical attention.

Oral: Low ingestion hazard in normal use. Although unlikely, if a gross ingestion of the dry powders occurs, when supplied as separate components, seek medical attention.

Physical: Spills are slippery - (liquid component).

Prolonged/Repeated Exposure Effects:

Silica is chemically inert and is a non-combustible mineral. Excessive and long-term exposure to silica dust may cause lung disease and silicosis.

Eye: Conjunctivitis of the eye is possible.

Skin: No known applicable information for the blended product. For dry powders, dermatitis of the skin is possible; avoid prolonged, repeated or excessive contact with skin. If contact is expected, wear gloves to avoid skin dryness or irritation.

Inhalation: No known applicable information for the blended product. Repeated inhalation of the dry powders can produce varying degrees of respiratory irritation. Crystalline silica is listed by NTP as a known human carcinogen, and it is classified by IARC in Group 1; materials for which there is sufficient evidence in humans for carcinogenicity. The adverse health effects – Silicosis, cancer, autoimmune diseases, tuberculosis, and nephrotoxicity are chronic effects. (When supplied as separate components).

<u>Silicosis</u>	Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death.
<u>Cancer</u>	Respirable crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans.
<u>Autoimmune Diseases</u>	There are some studies that show excess numbers of cases of scleroderma and other connective tissue disorders in workers exposed to respirable crystalline silica.
<u>Tuberculosis</u>	Silicosis increases the risk of tuberculosis.
<u>Nephrotoxicity</u>	There are some studies that show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

Oral: No known applicable information.

Signs and Symptoms of Overexposure:

No known applicable information.

Medical Conditions Aggravated by Exposure:

The condition of individuals with lung disease (e.g. bronchitis, emphysema, chronic obstructive pulmonary disease) can be aggravated by exposure to respirable crystalline silica (quartz). (When supplied as separate components). Also, exposure to the dry powder components of this product may aggravate conjunctivitis of the eye, dermatitis of the skin, asthma and other respiratory diseases.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of base products by others. Please refer to section 11 for the detailed toxicology.

SECTION 4. FIRST AID MEASURES

Eye:	Remove contact lenses if present, immediately flush with water, if irritation persists, seek medical attention. Abrasion to the cornea is possible.
Skin:	No first aid should be needed. When supplied as separate components, for dry powders, if irritation develops, area may be flushed with water and a mild soap may be used if available. If symptoms persist, contact a poison control center, emergency room or physician for treatment information.
Inhalation:	No first aid should be needed in normal use, however, when supplied as separate components, although unlikely, if there is a gross inhalation of respirable crystalline silica (quartz), remove the person immediately to fresh air, give artificial respiration as needed, seek medical attention as needed.
Oral:	No first aid should be needed in normal use, however, although unlikely, if a gross ingestion of the product or dry powders occur, gently wipe or rinse the inside of the mouth with water. Contact a poison control center, emergency room or physician for treatment information.
Comments:	Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

Flash Point:	212°F /100°C (Closed Cup). Prior to curing; liquid state
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire-exposed metal containers. (Prior to curing; liquid state.)
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep the fire exposed metallic containers cool. (Prior to curing; liquid state.) Avoid formation of dust clouds, when supplied as separate components.
Unusual Fire Hazards:	None.

Hazardous Decomposition Products:

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Metal oxides, carbon oxides, traces of incompletely burned carbon compounds, silicon dioxide, formaldehyde and quartz.

If crystalline silica (quartz) is heated to more than 1598 °F (870°C) it can change to a form of crystalline silica known as trydimite, and if crystalline silica is heated to more than 2646 °F (1470°C) it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up:

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8¹. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped store recovered material in appropriate container. For respirable crystalline silica (quartz)², when supplied as separate components, use dustless methods (vacuum) and place into closable container for disposal, or flush with water. Do not dry sweep. Wear protective equipment specified below.

Clean up remaining materials from spill with suitable absorbent. Clean area as appropriate since some silicone materials, even in small quantities, may present a slipping hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the clean up of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note 1: See Section 8 for personal Protective Equipment for spills.

Note 2: Substantially reduced when pre-blended material is supplied.

SECTION 7. HANDLING AND STORAGE

Use with adequate ventilation. When supplied as separate components, for the dry powders, avoid eye and skin contact, and contact with clothing; avoid generating respirable dust, do not breathe dust, or ingest.

Use reasonable care and store in dry, well ventilated areas away from oxidizing materials; keep containers closed.

Product evolves minute quantities of flammable hydrogen gas, which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Do not store in glass containers, which may shatter due to pressure build-up. Clogged container vents may increase build-up. Keep container closed and store from water or moisture.

For the dry powders, when supplied as separate components, avoid grinding, milling or otherwise generating respirable dust. When dust is present, keep airborne dust concentrations below PEL. Use adequate ventilation and dust collection. Do not rely on your sight to determine if dust is in the air. Dust may be in the air without a visible dust cloud. If dust cannot be kept below permissible limits, wear a respirator approved for the specific dust when using, handling, storing or disposing of this product or container. Practice good housekeeping. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. Maintain, clean, and fit test respirators in accordance with OSHA regulations. Maintain and test ventilation and dust collection equipment. Wash or vacuum clothing that has become dusty. See also control measures in Section 8.

Precautions During Storage

Keep containers closed; store in a dry, well ventilated area. Avoid breakage of containerized materials or spills of the dry powder material ³ when supplied as separate components. See also control measures in Section 8.

The OSHA Hazard Communication Standard, 29 CFR Sections 1910.1200, 1915.1200, 1917.28, 1918.28, 1926.59 and 1928.21, and state and local worker or community “right-to-know” laws and regulations should be strictly followed. **WARN YOUR EMPLOYEES (AND YOUR CUSTOMERS IN THE CASE OF RESALE) BY POSTING AND OTHER MEANS OF THE HAZARDS AND THE REQUIRED OSHA PRECAUTIONS. PROVIDE TRAINING FOR YOUR EMPLOYEES ABOUT THE OSHA PRECAUTIONS.**

See also the American Society for Testing and Materials (ASTM) standard practice E 1132-99a, “Standard Practice for Health Requirements Relating to Occupational Exposure to Respirable Crystalline Silica.”

Note 3: Substantially reduced when pre-blended material is supplied.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

See below.

Permissible Exposure Levels:

The following is for respirable crystalline silica (quartz), when supplied as separate components, :⁴

Material Identification			Exposure Guidelines						
Component	CAS No.	Percentage (by wt.)	OSHA PEL		ACGIH TLV		NIOSH REL		Unit
			TWA	STEL	TWA	STEL	TWA	STEL	
			Crystalline Silica (quartz)	14808-60-7	>99.0	10/%SiO ₂ +2	None	0.025	

Note 4: Substantially reduced when pre-blended material is supplied.

Engineering Controls

Local Ventilation⁵: Use sufficient local exhaust to reduce the level of respirable crystalline silica to below the PEL. See ACGIH “Industrial Ventilation, A Manual of Recommended Practice” (latest edition).

General Ventilation: Recommended.

Note 5: None should be needed when pre-blended material is supplied.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection – safety glasses as a minimum. If powder exposure to the eyes is likely, use tight fitting chemical safety goggles.

Skin: Washing at mealtime and at end of shift is adequate.

Suitable Gloves: No special protection needed for the blended product. For dry powders avoid prolonged, repeated or excessive contact with skin, if expected wear gloves to avoid skin dryness or irritation.

Inhalation: No respiratory protection should be needed for the blended product. For dry powders, the specific respirator must be based on the airborne concentration, (above PEL), found in the workplace and must not exceed the working limits of the respirator.

Suitable Respirator: Where respirable dust is present above permissible exposure limits, use appropriate NIOSH approved dust filter respirator.

Personal Protective Equipment for Spills

Eyes: Use proper protection – safety glasses as a minimum. If powder exposure to the eyes is likely, use tight fitting chemical safety goggles.

Skin: Washing at mealtime and at end of shift is adequate. For the dry powders, when supplied as separate components, avoid repeated exposure to the skin.

Inhalation /Suitable Respirator: See above.

Precautionary Measures: Avoid eye contact and/or the generation of dust clouds. Use reasonable care.

Comments: When heated to temperatures above 180°C (356°F) in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin, and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within OSHA Permissible Exposure Limit for formaldehyde. If crystalline silica (quartz) is heated to more than 1598 °F (870°C) it can change to a form of crystalline silica known as trydimite, and if crystalline silica is heated to more than 2646 °F (1470°C) it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

Note: These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Liquid
Color:	Off-White
Odor:	Not available
Specific Gravity @ 25°C	1.08
Viscosity:	6250 cSt
Freezing/Melting Point:	Not determined
Vapor pressure @25°C	>35C/95F
Vapor Density:	Not determined
Solubility In Water:	Not determined
pH:	Not determined
Volatile Content:	Not determined

When the product is supplied separate components, an additional component will be included and will have the following properties:

Appearance:	Sand granular, crushed or ground
Color:	White or tan
Odor:	None
Specific Gravity @ 25°C	2.65
Freezing/Melting Point:	Not determined
Vapor pressure (mm Hg)	None
Vapor Density (Air = 1):	None
Solubility In Water:	Insoluble in water
Melting Point	3110°F
Boiling Point:	4046°F
Evaporation Rate (Butyl Acetate =1):	None

Note: The above information is not intended for use in preparing product specifications. Contact PCI-Promatec before writing specifications.

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Hazardous polymerization will not occur under normal temperatures and pressures..
Conditions to avoid:	For the product after component blending, none known. For dry powder, generation of respirable dust. For crystalline silica exposure to temperatures >870°C may result in a more hazardous crystalline formation..
Materials to avoid:	Oxidizing material can cause a reaction. Water, alcohols, acidic or basic materials, and many metals or metallic compounds, when in contact with product, liberate flammable hydrogen gas, which can form explosive mixtures in air.
Incompatibility (Materials to Avoid):	For crystalline silica (quartz) contact with powerful oxidizing agents such as fluorine, chlorine trifluoride and oxygen difluoride may cause fires.
Hazardous Decomposition Products:	Silica will dissolve in hydrofluoric acid and produce a corrosive gas – silicon tetrafluoride. See also Section 8.

SECTION 11. TOXICOLOGICAL INFORMATION

Special Hazard Information on Components

For respirable crystalline silica (quartz):

A. Silicosis

The major concern is silicosis, caused by inhalation and retention of respirable crystalline silica dust. Silicosis can exist in several forms, chronic (or ordinary), accelerated, or acute.

Chronic or Ordinary Silicosis (often referred to as Simple Silicosis) is the most common form of silicosis, and can occur after many years of exposure to relatively low levels of airborne respirable crystalline silica dust. It is further defined as either simple or complicated silicosis.

Simple silicosis is characterized by lung lesions (shown as radiographic opacities) less than 1 centimeter in diameter, primarily in the upper lung zones. Often, simple silicosis is not associated with symptoms, detectable changes in lung function or disability.

Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF). Complicated silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than 1 centimeter in diameter. Although there may be no symptoms associated with complicated silicosis or PMF, the symptoms, if present, are shortness of breath, wheezing, cough and sputum production. Complicated silicosis or PMF may be associated with decreased lung function and may be disabling. Advanced complicated silicosis or PMF may lead to death. Advanced complicated silicosis or PMF can result in heart disease secondary to the lung disease (corpumomale).

Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; the lung lesions can appear within five (5) years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that the lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

B. CANCER

IARC – The International Agency for Research on Cancer (“IARC”) concluded that there was “sufficient evidence in humans for the carcinogenicity of crystalline silica in the forms of quartz or cristobalite from occupational sources”, and that there is “sufficient evidence in experimental animals for the carcinogenicity of quartz and cristobalite.” The overall IARC evaluation was that “crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is *carcinogenic to humans (Group 1)*.” The IARC evaluation noted that “carcinogenicity was not detected in all industrial circumstances studies. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs.” For further information on the IARC evaluation, see IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68, “Silica, Some Silicates...” (1997).

NTP – The National Toxicology Program, in its Ninth Annual Report on Carcinogens, classified “silica, crystalline (respirable)” as a known human carcinogen.

OSHA – Crystalline silica (quartz) is not regulated by the U.S. Occupational Safety and Health Administration as a carcinogen.

There have been many articles published on the carcinogenicity of crystalline silica, which the reader should consult for additional information; the following are examples of recently published articles: (1) “Crystalline Silica and Lung Cancer: The Problem of Conflicting Evidence”, Indoor Build Environ, Volume 8, pp. 121-176 (1998); (2) “Crystalline Silica and the risk of lung cancer on the potteries”, Occup. Environ. Med., Volume 55, pp. 779-785 (1998); (3) “Is Silicosis Required for Silica-Associated Lung Cancer?”, American Journal of Industrial Medicine, Volume 37, pp. 252-259 (2000); (4) “Silica, Silicosis, and Lung Cancer: A Risk Assessment”, American Journal of Industrial Medicine, Volume 38, pp. 8-18 (2000); (5) “Silica, Silicosis and Lung Cancer: A Response to a Recent Working Group Report”, Journal of Occupational and Environmental Medicine, Volume 42, pp. 704-720 (2000).

C. AUTOIMMUNE DISEASES

There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis is associated with the increased incidence of several autoimmune disorders, -- scleroderma, systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. For a review of the subject, the following may be consulted: “Occupational Exposure to Crystalline Silica and Autoimmune Disease”, Environmental Health Perspectives, Volume 107, Supplement 5, pp. 793-802 (1999); “Occupational Scleroderma”, Current Opinion on Rheumatology, Volume 11, pp. 490-494 (1999).

D. TUBERCULOSIS

Individuals with silicosis are at increased risk to develop pulmonary tuberculosis, if exposed to persons with tuberculosis. The following may be consulted for further information: Occupational Lung Disorders, Third Edition, Chapter 12, entitled “Silicosis and Related Diseases”, Parkes, W. Raymond (1994); “Risk of pulmonary tuberculosis relative to silicosis and exposure to silica dust in south African gold miners,” Occup Environ Med., Volume 55, pp. 496-502 (1998).

E. KIDNEY DISEASE

There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis is associated with the increased incidence of kidney diseases, including end stage renal disease. For additional information on the subject the following may be consulted: “Kidney Disease and Silicosis”, Nephron, Volume 85, pp. 14-19 (2000).

SECTION 12. ECOLOGICAL INFORMATION**Environmental Fate and Distribution**

Complete information is not yet available.

Environmental Effects

Complete information is not yet available, however, Crystalline silica (quartz) is not known to be ecotoxic; (i.e. there is no data which suggest that crystalline silica (quartz) is toxic to birds, fish, invertebrates, microorganisms or plants.) For additional information on crystalline silica (quartz), see Sections 9 (physical and chemical properties) and 10 (stability and reactivity) of this MSDS.

Fate and Effects in Waste Water treatment Plants

Complete information is not yet available

SECTION 13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as hazardous waste?

Yes.

Characteristic Waste:

Reactive: D003

Dispose of dry powder waste by any approved solid waste disposal method. Limit exposure so that it does not exceed OSHA standard TLV. Water may be used to limit dust.

State or local laws may impose additional regulatory requirements regarding disposal.

SECTION 14. TRANSPORT INFORMATION**DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations. VENTED PACKAGES FORBIDDEN FOR AIR TRANSPORT

SECTION 15. REGULATORY INFORMATION**RCRA Hazard Class (40 CFR 261)**

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or are exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings

Section 302 Extremely Hazardous Substances:

None

Section 304 CERCLA Hazardous Substances:

None

Section 312 Hazard Class:

Acute: No
Chronic: No, (liquid component); Yes, (dry powders)
Fire: No
Pressure: No
Reactive: Yes

Section 313 Toxic Chemicals

None present or none present in regulated quantities.

OSHA Carcinogen:

Crystalline silica (quartz) is NOT listed.

NTP:

Respirable crystalline silica, primarily quartz dusts occurring in industrial and occupational settings, is classified as Known to be a Human Carcinogen.

Canada

Domestic Substances List: Sub-supplier's products, as a naturally occurring substance, is on the Canadian DSL (crystalline silica (quartz)), and is exempt.

WHMIS Classification: D2A

Supplemental State Compliance Information

California

Warning: this product contains the following chemical(s) listed by the state of California under the safe drinking water and toxic enforcement act of 1986 (**Proposition 65**) as being known to cause cancer, birth defects or other reproductive harm.

Crystalline silica (quartz) – Carcinogen

California Inhalation Reference Exposure Level (REL)

California established a chronic REL of 3 ug for silica (crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

Massachusetts

No ingredient regulated by MA Right-to-Know Law Present (liquid component). No information available for the dry powders.

Massachusetts Toxic Use Reduction Act:

Silica, crystalline (respirable size, <10 microns) is “toxic” for the purposes of the Massachusetts Toxic Use Reduction Act.

New Jersey

<u>CAS number</u>	<u>Wt %*</u>	<u>Wt %**</u>	<u>Component Name</u>
70131-67-8	>60.0	>50.0	Dimethyl siloxane, hydroxy-terminated
63148-57-2	7.0 – 13.0	20.0 – 50.0	Methylhydrogen siloxane
14808-60-7	15.0 – 40.0	10.0 – 35.0	Quartz (Liquid Component)
68037-59-2	1.0 – 5.0	<5%	Dimethyl, methylhydrogen siloxane
68083-19-2	1.0 – 5.0	<5%	Dimethyl siloxane, dimethylvinyl-terminated
14808-60-7	>99%	15.0 – 20.0	Crystalline Silica (Dry Powder Component)
1344-28-1	<1%	<1%	Aluminum Oxide
13463-67-7	<1%	<1%	Titanium Oxide
1309-37-1	<1%	<1%	Iron Oxide

* When supplied as separate components. See sections 3 and 11 of this MSDS.

** When supplied premixed.

Pennsylvania

<u>CAS number</u>	<u>Wt %*</u>	<u>Wt %**</u>	<u>Component Name</u>
70131-67-8	>60.0	>50.0	Dimethyl siloxane, hydroxy-terminated
63148-57-2	7.0 – 13.0	20.0 – 50.0	Methylhydrogen siloxane
14808-60-7	15.0 – 40.0	10.0 – 35.0	Quartz (Liquid Component)
14808-60-7	>99%	15.0 – 20.0	Crystalline Silica (Dry Powder Component)
1344-28-1	<1%	<1%	Aluminum Oxide
13463-67-7	<1%	<1%	Titanium Oxide
1309-37-1	<1%	<1%	Iron Oxide

* When supplied as separate components. See sections 3 and 11 of this MSDS.

** When supplied premixed.

Other

EINECS No. 231-545-4/238-878-4 (Dry Powder)

EEC Label (Risk/Safety Phrases): R 48/20, R40/20, S22, S38 (Dry Powder)

IARC:	Crystalline Silica (Quartz) is classified in IARC Group 1.
Japan MITI:	The dry powder component of this product is an existing chemical substance as defined in the Chemical Substance Control Law.
Australian Inventory of Chemical Substances:	The dry powder component of this product is listed on the AICS inventory or exempt from notification requirements.

SECTION 16. OTHER INFORMATION

Prepared by: PCI-Promatec

These data are based on information supplied by the manufacturers of the base components. These data are offered in good faith. The manufacturer of the base components considers values shown herein to be typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.